

IBI GROUP 203–350 Oxford Street West London ON N6H 1T3 Canada tel 519 472 7328 fax 519 472 9354 ibigroup.com

# Memorandum

To/Attention	Municipality of Central Elgin, Asset Management and Development Services	Date	October 18, 2022
From	Sandra Hayman, P. Eng.	Project No	136299
СС			
Subject	384 George Street - Functional Servicing Brief		

# Introduction/Background

The site is located within the former Village of Port Stanley on the south side of George Street, approx. 200m west of the George/Front Street intersection. The site is 0.37 ha in size with residential properties to the east and west, and protected treed area to the south. Currently, the site has several residential buildings(cottages) with gravel driveways, treed area along the south portion of the site. The proposed development is a residential condominium, comprised of a townhouse block with five units and 3 single detached houses.

The site is located within the Kettle Creek watershed.

# Water Servicing

There is an existing 200mmØ PVC watermain in the George St right of way (ROW) on the south side. As per municipal standards, a new 50mmØ water service (development water main) will be installed, off the existing George St water main, inline with the proposed development entrance/lane. Each unit shall be serviced off the 50mmØ development water main with 25mmØ services and individual unit water meters, as per municipal standards. The existing hydrants located in George St ROW are approx. 95m west and approx. 100m east of the existing gravel entrance.

# Sanitary Analysis

There is an existing municipal 200mmØ sanitary sewer running beneath the roadway asphalt along George Street. This sewer will be utilized by installing a new maintenance hole on the existing sewer inline with the proposed lane into the site, and installing a new 200mmØ sanitary sewer connection into the site. There is a total of 8 units proposed for this site (townhouse with 5 units and 3 single detached units). As per municipality standards, total population is calculated with

3.0ppu per unit, which gives a total proposed population of 24. From the attached Sanitary Sewer Design Sheet, the total design flow is 0.38l/s.

#### Stormwater Management and Drainage

#### Criteria

This SWM brief addresses the storm drainage and stormwater management (SWM) aspects of this development and has been prepared in accordance with the recommendations and requirements of the following:

a) The Corporation of the Municipality of Central Elgin *Design Guidelines Manual*, 2022;

The peak flows discharged from the site shall not increase as a result of the proposed development for the calculated 2 through 100-year storm events. (see section 8.01 of the Central Elgin Design Guidelines Manual)

- b) The Municipality of Central Elgin's Asset Management and Development Services Department Design Specifications and Requirements;
- c) The Ministry of the Environment, Conservation and Parks' *Stormwater Management Planning and Design Manual,* March 2003.

#### Assumptions/Calculations

Following are stormwater calculations/assumptions for the site:

- The total drainage area for the site is calculated at 0.37 ha (the property area), which is sub-divided into three drainage areas. Area 101 drains to a roadside catch basin (CB) at the northwest corner of the property, area 102 drains to a roadside catch basin at the northeast corner of the property, and area 103 drains to an existing pond feature at the rear (southside) of the property.
- Figure 1 shows pre-development drainage conditions for the site. There are no external drainage areas noted. Calculations are attached to confirm the overall pre-development site runoff coefficient of 0.40. Runoff Coefficients for each individual drainage area are shown on the plan.
- The proposed post-development Runoff coefficients and Impervious values are shown in Figure 2, which is divided into areas that correspond to the existing drainage areas. Calculations are attached to confirm the overall post-development site runoff coefficient of 0.47. Runoff Coefficients for each individual drainage area are shown on the plan.
- The site grading plan has been designed to ensure that stormwater flows will be self-contained on site, up to the 100-year event, and safely conveys up to the 250-year storm event to the George St ROW.

- The rational method was used in the calculation of the critical storage volume required. Attached are the calculations for the 2-year, 5-year and 100-year events for each of the three areas. Due to the small drainage area, it is difficult to provide multiple orifice configurations to restrict post development flows to pre-development levels for each storm event. Therefore, the site has been designed to over-restrict flows for each event to the 2-year storm level, where possible.
- For the drainage area 101/201 post-development run off will be directed to a new CB 3 to be installed with a lead to the existing CB 1 in the adjacent ROW, which is connected to a 750mm storm sewer on the north side of George St (Known as the George St Drain). To restrict 100-year post development flows to 2-year pre-development levels, a mix of 4.75m<sup>3</sup> of surface ponding above the new CB 3 and 10.0m<sup>3</sup> underground storage in a rock trench will be provided to accommodate the calculated required storage of 13.0m<sup>3</sup>. Also, a 50mm Orifice will be installed on the outlet of the new CB 3.
- For the drainage area 102/202 post-development run off will be directed to a new CB 4 to be installed with a lead to the existing CB 2 in the adjacent ROW, which is connected to a 750mm storm sewer on the north side of George St (Known as the George St Drain). To restrict 100-year post development flows to 2-year pre-development levels, a mix of 6.13m3 of surface ponding above the new CB 4 and 5.0m3 underground storage in a rock trench to accommodate the calculated required storage of 11.0m3. Also, a 75mm Orifice will be installed on the outlet of the new CB 4.
- For the drainage area 103/203 post-development run off will be directed to the existing pond feature at the southeast of the development site. The calculated post development runoff for the 2-year, 5-year and 100-year storms are equal to the existing runoff, respectively. Therefore, no new mitigating measures are required.
- Sediment and Erosion Control Measures during construction are shown on the Conceptual Grading and Servicing drawing. The measures include silt fencing along the property limits in areas that ensure that sediment does not get washed onto the surrounding properties during storm events, as well as other measures as necessary such as straw bale filters, prompt reseeding of bare earth, and swales to direct flows etc. Monitoring during construction will be required to ensure proper maintenance of these measures.

#### Conclusion

The minimal increase in runoff for the 2-year to 100-year storm events will be accommodated with surface ponding and underground rock trenches.

4

The 250-year storm flow has been designed to be conveyed overland to the George St right of way.

Sediment and Erosion Control measures during construction are shown on the Conceptual Grading and Servicing drawing.

Sincerely,

**IBI Group** 

Sandra Hayman, P. Eng. Associate, Manager Civil Engineering SH/encl.

https://ibigroup.sharepoint.com/sites/Projects2/136299/Internal Documents/6.0\_Technical/6.03\_Tech-Reports/6.08.01/CTR-swm.docx

IBI GROUP MEMORANDUM

Municipality of Central Elgin, Asset Management and Development Services - October 18, 2022

# **FIGURES**











		CLIENT		]
		10007414 - Calib	er	
		Contracting		
	CEORGE ST			
		130 Shearson Cres, Cambridge,	ON N1T	
		1J4		
		COPYRIGHT	thus any	
Mark mark         Bit concerts         Bit concerts <th></th> <td>reproduction or distribution for any purpose other than authorized forbidden. Written dimensions shall have precedence over scale Contractors shall verify and be responsible for all dimensions and</td> <td>by IBI Group is ed dimensions. d conditions on</td> <td></td>		reproduction or distribution for any purpose other than authorized forbidden. Written dimensions shall have precedence over scale Contractors shall verify and be responsible for all dimensions and	by IBI Group is ed dimensions. d conditions on	
	AKE ERIE	the job, and IBI Group shall be informed of any variations from the conditions shown on the drawing. Shop drawings shall be submit for general conformance before proceeding with fabrica	dimensions and ted to IBI Group ation.	
		IBI Group Professional Services (Canad	a) Inc.	
Image: constraint of the second se		is a member of the IBI Group of companies		-
SEAL CONSULTANTS SEAL		No. DESCRIPTION	DATE	1
CONSULTANTS CONSUL		1 ISSUED TO MUNICIPALITY	2022-10-18	-
CONSULTATS  CONSULTATIS  CON				
CONSULTANTS CONSULTANTS CONSULTANTS CONSULTANTS SEAL SEAL SEAL PROJECT SEAL SE		at at		
CONSULTANTS CONSULTANTS CONSULTANTS SEEL SEEL SEEL SEEL SEEL SEEL SEEL SE		NA		
CONSULTANTS CONSULTANTS SEEAL SEAL SEEAL		INII		
CONSULTANTS CONSULTANTS SEAL		offly		
CONSULTANTS SEA. SEA. SEA. SEA. PROJECT NOC 136229 DRUG TANC 136229 DRUG TANC 136229 DRUG TANC 136229 DRUG TANC 136229 DRUG TANC 136229 DRUG TANC 136229 DRUG TANC 136229 DRUG TANC 136229 DRUG TANC SHEET TITLE CONCEPTUAL GRADING & SERVICING SHEET TITLE CONCEPTUAL GRADING & SERVICING SHEET NUMBER SHEET NUMER SHEET NUMBER SHEET NUMBER SHEET NUMBER		Pr.		
CONSULTANTS SEAL SEAL SEAL SEAL PROJECT MAGE STORES 384 George St 384 Geor				
CONSULTANTS SEAL				
CONSULTANTS SEAL SEAL SEAL SEAL PROJECT BIOLOGY SEAL PROJECT TO SEAL PROJECT TO SEAL PROJECT TO SEAL PROJECT TO SEAL CONCEPTUAL GRADING & SERVICING				
CONSULTANTS SEAL SEAL SEAL PROJECT Sub VID - 11 Advent Barent Sub VID - 11 Advent				
CONSULTANTS SEAL SEAL SEAL BIGROUP BURGOUP SEAL SEAL BIGROUP SEAL SE				
CONSULTANTS SEAL SEAL BIGROUP BIGRO				
CONSULTANTS SEAL				
CONSULTANTS SEAL SEAL SEAL But OUT 10 Albert Breat But OUT 10 Albe				
CONSULTANTS SEAL SEAL SEAL PROJECT Sealer of the Aber Street Sealer of				Valsh
SEAL SEAL SEAL SEAL SEAL SEAL SING OF PROJECT SING OF PROJECT NO: 13824 George St PROJECT NO: 13824 George St PROJECT NO: 13825 SHEET NUMBER SHEET NUMBER S		CONSULTANTS		edric V
SEAL SEAL Build OD - 410 Abert Street Wedge OD NV2, NO Calvet Subject ON NV2, NO Calvet Subject ON NV2, NO Calvet Subject PROJECT 384 George St PROJECT NO: 13829 PROJECT NO: 1384 George St PROJECT NO: 1384 GEORGE SHEET NUMBER SHEET NUMBER SHEET NUMBER SHEET NUMBER STATE SHEET NUMBER STATE STAT				l by Ce
SEAL SEAL SEAL SEAL SEAL SIDE SUBJECT 100 136299 PROJECT 384 George St 384 George St 384 George St 384 George St 384 George St 384 George St 384 George St 385 SEA SHEET NUMBER SHEET NUMBER SHEET NUMBER SHEET NUMBER 1 SUBJECT 1 SUBJECT 1 SUBJECT 1 SUBJECT 1 SHEET NUMBER 1 SUBJECT 1 SU				22 PN
SEAL SEAL BERNOUT Wester Divert Materi Street Wester Divert Materi Street Street Divert Materi Street Street Divert Materi Street Street NUL Street Materia Street Street Street Street Materia Street Street Street Street Street Street Street Street Street Street S				2:32:
SEAL SEAL BERNET Basisti - KII Aber Street Basisti - KII Aber Street B				3, 2022
SEAL SEAL BERNIT - IN Albert Streets Bit OFF - IN Albert Streets Bit O				ber 16
SEAL SEAL BI GROUP Sub Of 1-410 Abert Street Methods 222 Sub Of 1-410 Abert Street Sub				, Octo
PROJECT NO: 136299 PROJECT NO: 13629 SH		SEAL		lesday
Image: State of the state		SLAL		ted: Ti
Image: State of the state				Plot
Image: State of the state				Walsh
Image: State 101 - 410 Abbert Street Waterbook N X2L 3V3 Canada bigroup.com         PROJECT         384 George St         PROJECT NO: 138299         DRAWN BY:       CHECKED BY: SH         DRAWN BY:       CHECKED BY: SH         CJUW       SH         PROJECT MOR:       SH         DRAWN BY:       CHECKED BY: SH         DRAWN BY:       SH         SHEET TITLE       CONCEPTUAL GRADING & SERVICING         SHEET TITLE       CONCEPTUAL GRADING & SERVICING         SHEET NUMBER       ISUE         01       11				Cedric
Image: Stream of the stream				22, by
Image: Street				18, 20
Ist GROUP         Sub Constant Street         Water on NZL 3V3 Canada         to State on NZL 3V3 Canada         TOTE NO:         384 George St         PROJECT NO:         136299         DRAWIN BY:         CHECKED BY:         CONCEPTUAL GRADING &         SHEET TITLE         CONCEPTUAL GRADING &         SHEET NUMBER         SHEET NUMBER         ISSUE         01				tober '
Image: Strategy of the strategy				ed: Oc
Image: Starter in the image: Starte				st Sav
Image: True Note:       Im				g La
Image: Street				ND.dw
Image: Project Mathin       Image: Project Mathin       Image: Project Mathin       Image: Project Mathin         PROJECT       384 George St         PROJECT NO:       384 George St         PROJECT NO:       136299         DRAWN BY:       CHECKED BY:         CJDW       SH         PROJECT MGR:       APPROVED BY:         DG       SH         SHEET TITLE       CONCEPTUAL GRADING & SERVICING         SHEET NUMBER       ISSUE         01       1				6299-(
Image: Street Waterioo ON NZL 3V3 Canada to 519 985 2255 ibigroup.com         PROJECT         384 George St         PROJECT NO: 136299         DRAWN BY: CLECKED BY: CJDW         CJDW         SH         PROJECT MGR: SH         SHEET TITLE         CONCEPTUAL GRADING & SERVICING         SHEET NUMBER       ISSUE         1       1				ets\13
PROJECT 384 George St PROJECT 384 George St PROJECT NO: 136299 DRAWN BY: CJDW SH PROJECT MGR: APPROVED BY: DG SH SHEET TITLE CONCEPTUAL GRADING & SHEET NUMBER SHEET NUMBER ISSUE 1		IBI GROUP Suite 101 - 410 Albert Street		vil\She
PROJECT 384 George St 384 George St PROJECT NO: 136299 DRAWN BY: CHECKED BY: CJDW SH PROJECT MGR: APPROVED BY: DG SH SHEET TITLE CONCEPTUAL GRADING & SERVICING SHEET NUMBER ISSUE 1		Waterloo ON N2L 3V3 Canada tel 519 585 2255	ł	04 Ci
PROJECT 384 George St 384 George St PROJECT NO: 136299 DRAWN BY: CHECKED BY: CJDW SH PROJECT MGR: APPROVED BY: DG SH SHEET TITLE CONCEPTUAL GRADING & SERVICING SHEET NUMBER ISSUE 1		ibigroup.com		Design
384 George St 384 George St 384 George St PROJECT NO: 136299 DRAWN BY: CHECKED BY: CJDW SH PROJECT MGR: APPROVED BY: DG SH SHEET TITLE CONCEPTUAL GRADING & SERVICING SHEET NUMBER ISSUE 1		PROJECT		7.03_[
384 George St         PROJECT NO:       136299         DRAWN BY:       CHECKED BY:         CJDW       SH         PROJECT MGR:       APPROVED BY:         DG       SH         SHEET TITLE       CONCEPTUAL GRADING & SERVICING         SHEET NUMBER       ISSUE         01       1		384 George St		uction/
384 George St         PROJECT NO:         136299       DRAWN BY:       CHECKED BY:         CJDW       SH         PROJECT MGR:       APPROVED BY:         DG       SH         SHEET TITLE       CONCEPTUAL GRADING &         CONCEPTUAL GRADING &       SERVICING         SHEET NUMBER       ISSUE         01       1				Produ
PROJECT NO: 136299 DRAWN BY: CHECKED BY: CJDW SH PROJECT MGR: APPROVED BY: DG SH SHEET TITLE CONCEPTUAL GRADING & SERVICING SHEET NUMBER ISSUE 1		384 George St		S\7.0
136299         DRAWN BY:       CHECKED BY:         CJDW       SH         PROJECT MGR:       APPROVED BY:         DG       SH         SHEET TITLE       CONCEPTUAL GRADING &         CONCEPTUAL GRADING &       SERVICING         SHEET NUMBER       ISSUE         1       1		PROJECT NO:		eorge
DRAWN BY: CHECKED BY: CJDW SH PROJECT MGR: APPROVED BY: DG SH SHEET TITLE CONCEPTUAL GRADING & SERVICING SHEET NUMBER ISSUE 1		136299		84_G(
Code     Sn       PROJECT MGR:     APPROVED BY:       DG     SH       SHEET TITLE     CONCEPTUAL GRADING &       SERVICING     SERVICING       SHEET NUMBER     ISSUE       01     1		DRAWN BY: CHECKED BY	(:	299_3
DG SH SHEET TITLE CONCEPTUAL GRADING & SERVICING SHEET NUMBER 1 SSUE 1		PROJECT MGR: APPROVED E	 3Y:	V:\136.
True North       Project North         SHEET TITLE         CONCEPTUAL GRADING &         SERVICING         SHEET NUMBER         ISSUE         1		DG SH		tion: V
True North Project North COINCEPTUAL GRADING & SERVICING SHEET NUMBER ISSUE 01 1				e Loca
True North Project North SHEET NUMBER ISSUE 1			A DV	Ē
True North Project North SHEET NUMBER ISSUE	( 4 ) ( 4 )			10mm
True North Project North SHEET NUMBER ISSUE				
	True North Project North			CHECK
				SCALE 1 in

# **SWM & SAN CALCULATIONS**

(updated Oct. 18/22)

	POPULATION DENSITIES		
		Lot Basis	Hectare Basis
LOW DENSITY	//SINGLE FAMILY	3.0 ppu	44 upha
MED. DENSIT	Y/SEMI-DETACHED	6.0 ppu	65 upha
HIGH DENSIT	Y	N/A ppu	N/A upha
COMMERCIAL		ppu	60 ppha
Institiual	(LIGHT - 20,000 l/h/d)	ppu	53 ppha
INDUSTRIAL	(HEAVY - 50,000 l/h/d)	ppu	150 ppha

#### SANITARY SEWER DESIGN SHEET (PRELIMINARY) DESIGN CRITERIA MUNICIPALITY OF CENTRAL ELGIN

SEWAGE	=	250.00 l/cap/day	0.0029	l/ha
SEWAGE (INCL. UNCE	ERTAI	NTY)	0.0032	l/ha
UNCERTAINTY	=	10%		
INFILTRATION	=	8640 l/ha/day	0.1000	l/s/ha
PEAKING FACTOR	=	1+(14/(4+P^.5)		

### PROJECT NAME: 384 George Street

	LOCATION				AREA			PO	PULAT	ION		S	EWAGE	FLOW	V		SEV	/ER DE	SIGN				PRC	OFILE			%
AREA	STREET	FROM	то	NET OR	DELTA	TOTAL	PER	PER	No. OF	DELTA	TOTAL	PEAKING.	INFIL.	SEW.	TOTAL	SIZE	n	SLOPE	CAP.	VEL.	LENGTH	FALL IN	Headloss	DROP	INVER	T ELEV.	CAPACITY
NO.				GROSS	HEC.	HEC.	HEC.	LOT	LOTS	POP.	POP.	FACT.	l/sec	l/sec	l/sec	mm		%	l/sec	m/sec	m	SEWER	u/s (m)	U/S MH	U.S.	D.S.	UTILIZED
101	Site	MH1	MH2	GROSS	0.37	0.37	132	3	8	24	24	4.37	0.04	0.34	0.38	200	0.013	1.00	32.67	1.04	53.8	0.538			178.279	177.741	1.16%

DATE	2022-10-17
DESIGN	CJDW
CHECKED	SH
PROJECT	136299

# **384 George Street** Port Stanley, ON

136299 October 18, 2022



#### Calculation of Runoff Coefficient

#### Pre Dev

Area ID		Area (ha)	C value	C*A	Timp	Timp*A
	Buildings	0.012	0.90	0.011	100%	0.0121
	Gravel Driveway	0.003	0.90	0.002	100%	0.0027
101	Open Space	0.072	0.25	0.018	0%	0
	Total	0.087		0.031		0.0148
	Average C/%Imp		0.36			17%
	Buildings	0.018	0.90	0.016	100%	0.0181
	Gravel Driveway	0.024	0.90	0.021	100%	0.0235
102	Open Space	0.051	0.25	0.013	0%	0
	Total	0.093		0.050		0.0416
	Average C/%Imp		0.54			45%
	Buildings	0.011	0.90	0.010	100%	0.011
	Gravel Driveway	0.018	0.90	0.016	100%	0.018
103	Open Space	0.156	0.25	0.039	0%	0
	Total	0.186		0.065		0.029
	Average C/%Imp		0.35			16%
Overa	II Average C/%Imp	0.365	0.40			23%

#### Post Dev

Area ID		Area (ha)	C value	C*A	Timp	Timp*A
	Buildings	0.034	0.90	0.031	100%	0.0344
	Asphalt Lane	0.011	0.90	0.010	100%	0.0109
201	Open Space	0.048	0.25	0.012	0%	0
	Total	0.093		0.053		0.0453
	Average C/%Imp		0.57			49%
	Buildings	0.030	0.90	0.027	100%	0.0301
	Asphalt Lane	0.011	0.90	0.010	100%	0.0111
202	Open Space	0.067	0.25	0.017	0%	0
	Total	0.108		0.054		0.0412
	Average C/%Imp		0.50			38%
	Buildings	0.027	0.90	0.024	100%	0.027
	Asphalt Lane	0.008	0.90	0.007	100%	0.008
203	Open Space	0.129	0.25	0.032	0%	0
	Total	0.164		0.064		0.0350
	Average C/%Imp		0.39			21%
Overa	II Average C/%Imp	0.365	0.47			33%

Port Stanley, ON October 18/22 136299

# ΙΒΙ

# **PreDevelopment Flow Calculations**

# Rainfall Intensity Parameters (From Central Elgin Draft Design Guidelines 2021)

	100 yr	5yr	2yr
A =	51.5	31.1	23.6
B =	-0.699	-0.699	-0.699
=	A*t <sup>B</sup>	Yarnell Forn	nula

# Area 101 (PreDev-Existing Flows)

A =	0.0869 Ha	
C =	0.36	
T =	15 min	
T =	0.25 hr	
I <sub>(100yr)</sub> =	135.72 mm/hr	(From Central Elgin Draft Design Guidelines 2021)
I <sub>(5yr)</sub> =	81.96 mm/hr	(From Central Elgin Draft Design Guidelines 2021)
I <sub>(2yr)</sub> =	62.19 mm/hr	(From Central Elgin Draft Design Guidelines 2021)
Qp <sub>(100yr)</sub> =	11.83 l/s	
Qp <sub>(5yr)</sub> =	7.14 l/s	
Qp <sub>(2yr)</sub> =	5.42 l/s	

#### **IBI GROUP**

Stormwater Management Rational Method Municipality of Central Elgin IDF requirements

Area 201



# **Design Criteria**

# Calculate Total Storage needed

#### to restrict 100 yr flows to 2 year storm predev levels

IBI

Area = Predevelopment C = IDF Curve = Predevelopment Tc = I =	0.093 hectares 0.36 100 year 15.00 minutes 134.67 mm/hr
Outflow Restriction =	0.005 cms (2 year predev flow)
Post Development C =	0.57

# **Calculation of Critical Storage Volume**

Rainfall	Rainfall	Peak		Release	Required
Duration	Intensity	Runoff	Storm	Flow	Storage
(min)	(mm/hr)	(m³/s)	Runoff (m <sup>3</sup> )	(m <sup>3</sup> )	(m <sup>3</sup> )
5	292.52	0.04	13	2	11
10	180.19	0.03	16	3	13
15	135.72	0.02	18	5	13
20	111.00	0.02	20	7	13
30	83.60	0.01	22	10	12
40	68.37	0.01	24	13	11
50	58.50	0.01	26	16	9
60	51.50	0.01	27	20	8
70	46.24	0.01	28	23	6
80	42.12	0.01	30	26	4
90	38.79	0.01	31	29	1
100	36.04	0.01	32	33	-1
110	33.71	0.00	33	36	-3
120	31.72	0.00	33	39	-6

Required On Site Storage =	13	m³
for the	100	Yr Storm

Port Stanley, ON October 18/22 136299

# ΪΒΙ

# **PreDevelopment Flow Calculations**

# Rainfall Intensity Parameters (From Central Elgin Draft Design Guidelines 2021)

	100 yr	5yr	2yr
A =	51.5	31.1	23.6
B =	-0.699	-0.699	-0.699
=	A*t <sup>B</sup>	Yarnell Forn	nula

# Area 102 (PreDev-Existing Flows)

A =	0.0929 Ha	
C =	0.54	
T =	15 min	
T =	0.25 hr	
I <sub>(100yr)</sub> =	135.72 mm/hr	(From Central Elgin Draft Design Guidelines 2021)
I <sub>(5yr)</sub> =	81.96 mm/hr	(From Central Elgin Draft Design Guidelines 2021)
I <sub>(2yr)</sub> =	62.19 mm/hr	(From Central Elgin Draft Design Guidelines 2021)
Qp <sub>(100yr)</sub> =	18.97 l/s	
Qp <sub>(5yr)</sub> =	11.45 l/s	
Qp <sub>(2yr)</sub> =	<mark>8.69</mark> l/s	

# Design CriteriaArea 202Calculate Total Storage neededto restrict 100 yr flows to 2 year storm predev levelsArea =0.093 hectaresArea =0.093 hectaresPredevelopment C =0.54IDF Curve =100 yearPredevelopment Tc =15.00 minutesI =134.67 mm/hrOutflow Restriction =0.009 cms (2 year predev flow)Post Development C =0.57

# **Calculation of Critical Storage Volume**

Rainfall	Rainfall	Peak		Release	Required
Duration	Intensity	Runoff	Storm	Flow	Storage
(min)	(mm/hr)	(m³/s)	Runoff (m <sup>3</sup> )	(m <sup>3</sup> )	(m <sup>3</sup> )
5	292.52	0.04	13	3	10
10	180.19	0.03	16	5	11
15	135.72	0.02	18	8	10
20	111.00	0.02	20	10	9
30	83.60	0.01	22	16	6
40	68.37	0.01	24	21	3
50	58.50	0.01	26	26	0
60	51.50	0.01	27	31	-4
70	46.24	0.01	28	37	-8
80	42.12	0.01	30	42	-12
90	38.79	0.01	31	47	-16
100	36.04	0.01	32	52	-20
110	33.71	0.00	33	57	-25
120	31.72	0.00	33	63	-29

Required On Site Storage =	11	m³
for the	100	Yr Storm

Port Stanley, ON October 18/22 136299

# ΙΒΙ

# **PreDevelopment Flow Calculations**

# Rainfall Intensity Parameters (From Central Elgin Draft Design Guidelines 2021)

	100 yr	5yr	2yr
A =	51.5	31.1	23.6
B =	-0.699	-0.699	-0.699
=	A*t <sup>B</sup>	Yarnell Forn	nula

# Area 103 (PreDev-Existing Flows)

C = 0.35	
T = 15 min	
T = 0.25 hr	
I <sub>(100yr)</sub> = 135.72 mm/hr (From Central Elgin Draft Design Guide	lines 2021)
I <sub>(5yr)</sub> = 81.96 mm/hr (From Central Elgin Draft Design Guide	lines 2021)
I <sub>(2yr)</sub> = 62.19 mm/hr (From Central Elgin Draft Design Guide	lines 2021)
Qp <sub>(100yr)</sub> = 24.69 l/s	
Qp <sub>(5yr)</sub> = 14.91 l/s	
Qp <sub>(2yr)</sub> = <u>11.32</u> l/s	

Port Stanley, ON October 18/22 136299

# 

# **Post Development Flow Calculations**

# Rainfall Intensity Parameters (From Central Elgin Draft Design Guidelines 2021)

	100 yr	5yr	2yr
A =	51.5	31.1	23.6
B =	-0.699	-0.699	-0.699
=	A*t <sup>B</sup>	Yarnell Forn	nula

# Area 203 (PostDev-Proposed Flows)

A =	0.164 Ha	
C =	0.39	
T =	15 min	
T =	0.25 hr	
I <sub>(100yr)</sub> =	135.72 mm/hr	(From Central Elgin Draft Design Guidelines 2021)
I <sub>(5yr)</sub> =	81.96 mm/hr	(From Central Elgin Draft Design Guidelines 2021)
I <sub>(2yr)</sub> =	62.19 mm/hr	(From Central Elgin Draft Design Guidelines 2021)
Qp <sub>(100yr)</sub> =	24.05 l/s	
Qp <sub>(5yr)</sub> =	14.53 l/s	
Qp <sub>(2yr)</sub> =	11.02 l/s	

Project:384 George StLocation:Port Stanley, ONDate:October 13/22Job No.136299

# **Orifice Calculation**

Location	Orifice Size (mm)	Orifice Area A (m2)	ĸ	h (m)	Qr (cms)	Required Qr (predev 2 yr flow) (cms)
CB Area 201	50	0.002	0.6	1.09	0.005	0.005

Orifice Invert = 178.50 m Max Ponding Elev = 179.61 m Therefore use a 50mm dia orifice.

# Storage Volume Drainage Area 201

Volume Required 13 m<sup>3</sup>

# CB3 stage storage

Elevation (m)	Area (m²)	Average End Volume (m <sup>3</sup> )	Total Average End Storage (m <sup>3</sup> )
179.30	0.36		
179.35	1.89	0.06	0.06
179.40	6.02	0.20	0.25
179.45	12.60	0.47	0.72
179.50	21.20	0.85	1.56
179.55	31.61	1.32	2.88
179.60	43.05	1.87	4.75

# Rock Trench

Width	1 m
Height	1 m
Length	25 m
Void Ratio	0.4
Rock Trench Volume	10 m <sup>3</sup>
Total Volume Provided	14.75 m <sup>3</sup>

Project:384 George StLocation:Port Stanley, ONDate:October 13/22Job No.136299

# **Orifice Calculation**

Location	Orifice Size (mm)	Orifice Area A (m2)	ĸ	h (m)	Qr (cms)	Required Qr (predev 2 yr flow) (cms)
CB Area 202	75	0.004	0.6	0.63	0.009	0.009

Orifice Invert = 178.68 m Max Ponding Elev = 179.35 m Therefore use a 60mm dia orifice.

# Storage Volume for Drainage Area 202

# Volume Required 11 m<sup>3</sup>

# CB4 stage storage

Elevation (m)	Area (m²)	Average End Volume (m <sup>3</sup> )	Total Average End Storage (m <sup>3</sup> )
179.05	0.36		
179.10	2.30	0.07	0.07
179.15	7.44	0.24	0.31
179.20	15.83	0.58	0.89
179.25	21.20	0.93	1.82
179.30	43.39	1.61	3.43
179.35	64.70	2.70	6.13

## Rock Trench

Width	1 m
Height	0.5 m
Length	25 m
Void Ratio	0.4
Rock Trench Volume	5 m <sup>3</sup>
Total Volume Provided	11.13 m <sup>3</sup>